

DYBBØL RING CHANDELIER





DYBBØL RING CHANDELIER

The DYBBØL RING CHANDELIER luminaire is designed with the fundamental idea that lighting should not dominate the space. The result is a simple, discreet, yet highly efficient lighting solution.

The ring chandelier is equipped with the DYBBØL luminaire, featuring a straightforward and functional design. The luminaire uses GU10 reflector light sources, ensuring a wide range of beam angles and excellent CRI properties. Additionally, the light sources are available in dimmable versions, further enhancing light quality. To minimize the risk of glare discomfort, the luminaire is fitted with a glare shield.

The DYBBØL luminaire is also available in other mounting solutions, such as rod-mounted fixtures, and the ring can be customized into other shapes, such as an ellipse.

Material & finish: Lacquered brass - polished, matt or grafital grey.

Dimension: Length 130 cm. - 730 cm. Distance between lamps 100 cm. More than two baton parts

Light sources: 2-8 HI Spot ES63 halogen reflector lamps.

Socket/holder: GU10. Wattage: Max. 75 W. 230 V.

Lysteknik: The chandelier provides functional downlighting, with glare discomfort minimized by shielding direct visibility of the light source. The selection of GU10 light sources offers extensive possibilities for optimizing lighting comfort.

Suspension: Wire or Pendant tubes

Safety classifications: I.

Ingress protection: IP20.

Remark: Customized solutions available upon request.
Design: AndersenLysdesign

Latest update: 28/02-2025