

KRONBORG CEILING





KRONBORG CEILING

The Kronborg Ceiling is an exclusive fixture that, with its minimalist design, offers great adaptability to all types of architecture.

Its premium brass finish adds an elegant and refined look to any space, while the white-lacquered version seamlessly integrates into environments where a discreet presence is desired—providing effective and pleasant illumination without dominating the setting.

The design, featuring a glare shield around the light source, prevents direct glare discomfort. Additionally, the ring provides reflectance, contributing to a decorative illumination of the fixture itself.

KRONBORG CEILING is ideal for illuminating counters, walkways, and foyer areas but is also well-suited for general lighting in both large and small spaces, such as conference rooms.

Material & finish: Polished and lacquered brass or White lacquered (RAL 9010)

Dimension: Shade diameter: ø50 mm. Height: 76 mm

Light sources: Socket/holder: G9. Wattage: 25W. 230V

Lysteknik: The ceiling fixture provides an exclusive and functional light. The glare shield ensures glare-free illumination for passersby, while the downward-facing opening allows for 100% downward-directed light. Additionally, the glare shield's reflectance from the light source contributes to a decorative illumination of the fixture

Suspension: Mounting on PL-junction box

Safety classifications: I.

Ingress protection: IP20.

Approval: CE-marking

Design: Hans Grønlund

Latest update: 28/02-2025