

LINAA DOWNLIGHT









LINAA DOWNLIGHT

The Linaa Downlight is a decorative and well-designed downlight, highly suitable for walkways, foyers, or as general lighting in spaces where floor flexibility is essential.

It is mounted flush-recessed, integrated into the ceiling. The small shielding prevents direct visibility of the light source, ensuring glarefree illumination when passing by.

The light source is installed from below and comes with a 2700K light source and a CRI of 90.

The fixture is discreet yet adds character to the ceiling, whether used as general lighting or in a corridor layout.

Particularly suitable for areas where luminaires contribute to enhancing the room's interior design.

Produkt: LINAA DOWNLIGHT

Material & finish: Polished and lacquered brass

Dimension: Ø7.6 cm / Ø13 cm. Cut-out diameter: Ø10 cm. Height of

the brass shade: 2.65 cm.

Light sources: LED, 8,5W, 610lm, 2700K, 42°, CRI 90, 230V,

dimmable

Lysteknik: The fixture provides direct downlighting. A 2.65 cm shade prevents direct glare from the light source when passing by. 2700K, CRI 90 ensures optimal and comfortable illumination.

Suspension: Recessed into the ceiling.

Safety classifications: II Ingress protection: IP20 Approval: CE-marking

Remark: Customised solutions available upon request

Design: AndersenLysdesign



Latest update: 17/03-2025